



# Proficiency Testing Planning of 2025

## TEXTILE

Accreditation **ISO/IEC 17043:2023**

Actualisé le 28/11/2025 :

**We are Testing and Proficiency testing provider. For a wide range of selection proficiency testing schemes, TTS PT is accredited ISO/IEC17043 (please look to our scoop of accreditation).**

Proficiency testing schemes that are not covered by the scope of accreditation are marked by the symbol  $\alpha$  in the catalogue and on the homepage.

### **WHY PARTICIPATING WITH TTS PT ?**

Our proficiency testing scheme cover a wide range of accredited tests and analysis. By participating in our proficiency testing scheme, you can evaluate the quality of your results and the performance of your routine testing method.

### **STATISTICS**

For qualitative test results we use median or mode depending on result distribution.

For quantitative tests we use algorithm A, outliers are determined after statistical and graphical analysis. (please see our statistical protocol).

### **EASY QUICK**

- Please register your laboratory contact informations
- Check your choice in our planning
- Send the filled registration form to: [C43@ttesting.org](mailto:C43@ttesting.org).

## SPECIAL DISCOUNT



**If you register for a large number of Proficiency tests, A special package deal will be offered! Take advantage of this exclusive offer!**

*By participating in all the tests in a single round, you'll receive a SPECIFIC discount. Don't miss out on this unique opportunity to save while enhancing your performance !*

<b>PT Round : TTS-T2501</b>				
	<b>Scope</b>	<b>Standard</b>	<b>Price €</b>	<b>Add Sample €</b>
<input type="checkbox"/>	Bursting properties of fabrics ☞	ISO 13938-2 : Bursting strength and bursting distension.	150	70
<input type="checkbox"/>	Colour fastness	ISO 105-E04/ GB/T 3922/ AATCC 15 : Colour fastness to perspiration.	110	50
<input type="checkbox"/>	Colour fastness	ISO 105-B02 : Colour fastness to artificial light : Xenon arc.	110	50
<input type="checkbox"/>	Colour fastness	ISO 105-C06 : Colour fastness to domestic and commercial laundering	110	50
<input type="checkbox"/>	Colour fastness ☞	ISO 105-X12 / GB/T 3920 / AATCC08 : Colour fastness to rubbing	150	70
<input type="checkbox"/>	Quantitative chemical analysis of fiber blend	ISO 1833-7 , GB/T 2910.parts : Mixtures of polyamide with certain other fibers (formic acid method)	200	100
<input type="checkbox"/>	Determination of pH	ISO 3071 : pH value of textiles	200	100
<input type="checkbox"/>	Tear properties of fabrics	ISO 13937-1 : Tear proprieties - Elmendorf method.	150	70
<input type="checkbox"/>	Protective clothing ☞	ISO 15025 : Limited flame spread	250	70
<input type="checkbox"/>	High visibility clothing ☞	ISO 20471 p 5.1 & p 5.2 : Requirements concerning the base materials, non-fluorescent materials, and materials with combined characteristics.	250	100

**PT Round : TTS-T2502**

	<b>Scope</b>	<b>Standard</b>	<b>Price €</b>	<b>Add Sample €</b>
<input type="checkbox"/>	<i>Determination of fabric propensity to surface pilling, fuzzing or matting</i>	<b>ISO 12945-2</b> : Determination of fabric propensity to surface pilling, fuzzing or matting - Martindale method.	150	70
<input type="checkbox"/>	<i>Protective clothing</i> ☒	<b>EN 348 / ISO 9150</b> : Determining the behaviour of fabrics to small splashes of molten metal by counting the number pf droplets.	250	100
<input type="checkbox"/>	<i>Determination of dimensional change in washing and drying</i> ☒	<b>ISO 5077 &amp; ISO 6330</b> : Determination of dimensional change in washing and drying & Domestic washing and drying procedures for textile testing.	150	70
<input type="checkbox"/>	<i>Quantitative chemical analysis of fiber blend</i>	<b>ISO 1833-11</b> : Mixtures of certain cellulose fibers with certain other fibers (sulfuric acid method)	200	100
<input type="checkbox"/>	<i>Protection against liquid chemicals</i> ☒	<b>ISO 14419</b> : Oil repellency – Hydrocarbon resistance test	250	100

**PT Round : TTS-T2503**

	<b>Scope</b>	<b>Standard</b>	<b>Price €</b>	<b>Add Sample €</b>
<input type="checkbox"/>	Determination of tensile properties for fabric/seam	ISO 13934-1: Tensile properties - strip method	150	70
<input type="checkbox"/>	Determination of tensile properties for fabric/seam	ISO 13935-1 : Maximum force to seam.	150	75
<input type="checkbox"/>	Determination of the abrasion resistance of fabrics	ISO 12947-4 : Determination of the abrasion resistance of fabrics by the Martindale method Part 4: Assessment of appearance change	150	75
<input type="checkbox"/>	Determination of tensile properties for fabric/seam	ISO 13936-1:Slippage resistance of yarns - Fixed seam opening method	150	75
<input type="checkbox"/>	Quantitative chemical analysis of fiber blend	ISO 1833-12 : Proportion of acrylic fibers	150	75
<input type="checkbox"/>	Determination of resistance to water penetration	ISO 811 :Determination of resistance to water penetration Hydrostatic pressure test.	150	70
<input type="checkbox"/>	Quantitative chemical analysis of fiber blend	ISO 1833-6 , GB/T 2910 : Mixtures of viscose, certain types of cupro, modal or lyocell with certain other fibers (formic acid and zinc chloride method)	200	70
<input type="checkbox"/>	Colour fastness	ISO 105-E02: Colour fastness to sea water	110	70
<input type="checkbox"/>	Colour fastness	ISO 105-E03 : Colour fastness to chlorinated water (swimming-pool water)	110	70
<input type="checkbox"/>	Determination of tensile properties for fabric/seam	ISO 13935-2 : Maximum force to seam - Grab method.	150	70
<input type="checkbox"/>	Determination of resistance to water penetration	ISO 4920 / AATCC 22 : Determination of resistance to surface wetting	150	70
<input type="checkbox"/>	Colour fastness ☒	ISO 105-X05 : Colour fastness to organic solvents	150	70
<input type="checkbox"/>	Tear properties of fabrics	ISO 4674-1 (Method B) : Constant rate of tear methods	150	75
<input type="checkbox"/>	Determination of tensile properties for fabric/seam	ISO 1421 (Method 1) : Determination of tensile strength and elongation at break	150	75

**PT Round : TTS-T2504**

	<b>Scope</b>	<b>Standard</b>	<b>Price €</b>	<b>Add Sample €</b>
<input type="checkbox"/>	Electrostatics proprieties ☒	EN 1149-1 : Test method for measurement of surface resistivity	250	100
<input type="checkbox"/>	Tear properties of fabrics	ISO 13937-2 : Tear properties - Trousers-shaped specimens	150	70

**YOUR LABORATORY INFORMATIONS**

<b>Contact Person</b>	
<b>Contact Person fonction</b>	
<b>Email</b>	
<b>Company name</b>	
<b>Company adress</b>	
<b>Street</b>	
<b>Post code</b>	
<b>Country</b>	
<b>VAT – ID</b>	

### ADDITIONAL SAMPLES

**Proficiency Test**

### SHIPMENT DETAILS

- All prices are mentioned in euro. Prices do not include shipping costs.
- Schipement Cots : **40 €**
- The customer is hereby informed that shipment of the sample by TTS PT will be at the customer's charge, including customs clearance costs if necessary.

### PLANNING

- In the tables above each Proficiency test has been allocated to a fixed test period respectively to a fixed time planning.

<b>Round 1</b>	Proficiency Tests with the period <b>March 2025</b>
<b>Round 2</b>	Proficiency Tests with the period <b>June 2025</b>
<b>Round 3</b>	Proficiency Tests with the period <b>September 2025</b>
<b>Round 4</b>	Proficiency Tests with the period <b>December 2025</b>